


LED & CO Datasheet

Cloche / Village





Cloche / Village LED-Light


Decorative Cloche LED-Light

Lamp case made of high quality recyclable aluminium die casting.

Equipped with a replaceable LED module with wide-beaming patented nano-optics. Comes with standard neutral white light (4.300 K), - other light colours on request - and a colour rendering index of $Ra > 75$.

Optional with CLO "Constant Light Output", a programmable night setback, depending on the actual situation on site.

Dimensions:



	Cloche / Village
Height (H)	490 mm
Diameter (D)	480 mm
Weight	5,4 kg

Details:

- ✓ Protection class: II oder I
- ✓ Operating voltage: 160-270 Volt
- ✓ $\cos \varphi: \geq 0.96$ full load value,
 ≥ 0.92 at lowering
- ✓ Start-up peaks 70A for 120 μ s
- ✓ Ripple current 30% at 50% lowering
- ✓ Autom. temperature monitoring
- ✓ Protection category: IP 54
- ✓ Cable feedthrough IP 68
- ✓ Lifespan of LED-module: ≥ 60.000 hours
- ✓ Montage: R 1/2
- ✓ Percentage of light in lower half-space: 100,0%
- ✓ CE

	Village 12	Village 16	Village 20	Village 24
Power Input:	max. 15W	max. 21W	max. 26W	max. 31W
Light Output:	1.280 lm	1.920 lm	2.398 lm	2.890 lm
Number of LEDs:	6	8	10	12

Optional:

- Dimming switch: 1-10V
- Night setback
- Warm white 3.500 Kelvin
Cold white 6.000 Kelvin
- Overvoltage protection: 10kV/ 4kV standard
- Mast top collar-piece
- RAL - colour of choice

Light distribution:

Optic asymmetric

